

Middle CNCTurn-Mill Machine (Product No: CX500)



Technical Parameters

Max Spindle Speed	3500 rpm (4000 max)	
Finish after machining	1.6Ra	
Spindle hole	25 mm	
Repeat positioning accuracy	±0.01 mm	
Unilateral cutting amount	2mm (3mm max)	
Spindle Power	3.7Kw Servo motor	
X/Z Axis Motor	1.2Kw Servo motor	
Y Axis Motor	1.2Kw Servo motor	
Power head	3 tools standard	4 tools optional
X Axis Travel	500 mm	
Z Axis Travel	80 mm	
Fast feed rate	20m/min (30m/min max)	
Clamping Diameter	Hydraumaticφ40mm(φ50 max)	
Cutting Feed Rate	0.001-500 mm/rev	
Cutting Length	180 mm	
Cutting Length With Lathe Center Frame	120 mm	
Machine Bed Inclination	30°	
Controller	Yornew Industrial CNC Controller	
Ball Screw	Taiwan P4	
Linear Guide	Taiwan P4 Linear Guide rail	
N / G Weight	1800-2200 kg	
Machine Size	1700*1200*1800mm	
Packing Size	1950*1300*2050mm	

YORNEW[®]

— Small CNC Machine —



Whats QR code

Yornew Automation Equipment Co., Ltd.

+86 757-25566186 +86 15916123639

manager@yornew.com

www.miumachine.com www.yornew.com

Phase 10, Tianfulai Hardware Park, No. 25, Xinfu Road, Ronggui, Shunde District, Foshan City, Guangdong, P.R.C.



Wechat QR code